

20-100 Oil Resistant Smooth Nitrile Gloves



EN388 STANDARDS						
Abrasion	1	2	3	4	-	1-1
Cut Resistance (Coup Test)	1	2	3	4	5	Χ*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	21	-
Cut Resistance (TDM Test)	Α	В	С	D	Ε	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Smooth Nitrile Coating Oil Resistant Water Resistant Abrasion Resistant



13 Gauge Liner Light & Breathable

Logo Customization

Knit Wrist Better fit

Color-Coded Bands
Distinguish sizes

SPECIFICATIONS Gauge 13 Liner Material Polyester Dip Material Smooth Nitrile Cuff Style Knit Wrist

RECOMMENDED APPLICATIONS

- Automotive
- Mechanical
- Construction
- Manufacturing

MEASURE HAND AT
SPECIFIED POINTS AND
MATCH MEASUREMENT TO
APPROPRIATE SIZE RANGE.*
*Sizing is partially based on

preference which can vary by glove material and application.

SIZE	WIDTH	LENDGH 6-3/4"- 7-1/4" 171 mm-183 mm		
S	2-15/16"- 3-1/4" 74 mm-84 mm			
М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8' 193 mm-203 mm		
L	3-13/16"- 4-1/4" 97 mm-107 mm	7-5/8"-8" 97 mm-107 mn		
XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm		
XXL	4-5/8"- 5' 216 mm-229 mm	4-5/8"- 5' 216 mm-229 mm		

