

20-540 MAX FLEXIBLE FOAM NITRILE GLOVES



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	Χ*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	Α	В	С	D	Е	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Foam Nitrile Coating
Oil Resistant
Slip Resistant
Wear Resistant
Superior Dexterity



15 Gauge Liner Highest dexterity

Logo Customization


Color-Coded Bands
Distinguish sizes

Knit Wrist Better fit

SPECIFICATIONS				
Gauge	15			
Liner Material	Nylon & Spandex			
Dip Material	Foam Nitrile			
Cuff Style	Knit Wrist			

RECOMMENDED APPLICATIONS

- Automotive
- Electronics
- Construction
- Mechanical
- General purpose working



SIZE	WIDTH	LENDGH
S	2-15/16"- 3-1/4" 74 mm-84 mm	6-3/4"- 7-1/4" 171 mm-183 mm
М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8' 193 mm-203 mm
L	3-13/16"- 4-1/4" 97 mm-107 mm	7-5/8"-8" 97 mm-107 mm
XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm
XXL	4-5/8"- 5' 216 mm-229 mm	4-5/8"- 5' 216 mm-229 mm

