

20-540M MAX FLEXIBLE MICRO-FOAM NITRILE GLOVES



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	Χ*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	Α	В	С	D	Ε	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Micro-foam Nitrile Coating Slip Resistant

Slip Resistant Wear Resistant Superior Dexterity More Light



15 Gauge Liner Highest Dexterity

Logo Customization


Knit Wrist Better Fit

> Color-Coded Bands Distinguish Sizes

SPECIFICATIONS Gauge 15 Liner Material Nylon & Spandex Dip Material Micro-foam Nitrile Cuff Style Knit Wrist

RECOMMENDED APPLICATIONS

- Automotive
- Electronics
- Construction
- Mechanical
- General purpose working



glove material and application.

SIZE	WIDTH	LENDGH
S	2-15/16"- 3-1/4" 74 mm-84 mm	6-3/4"- 7-1/4" 171 mm-183 mm
М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8' 193 mm-203 mm
L	3-13/16"- 4-1/4" 97 mm-107 mm	7-5/8"-8" 97 mm-107 mm
XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm
XXL	4-5/8"- 5' 216 mm-229 mm	4-5/8"- 5' 216 mm-229 mm

