

20-544 **ULTRA-THIN FOAM NITRILE GLOVES**



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	Х*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	Α	В	С	D	Е	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Foam Nitrile Coating Slip Resistant Wear Resistant Superior Dexterity

Embossed Style Better slip resistant

Knit Wrist Better Fit



Logo Customization

15 Gauge Mix Color

Nylon Spandex Liner

Color-Coded Bands Distinguish Sizes

SPECIFICATIONS				
Gauge	15			
Liner Material	Nylon & Spandex			
Dip Material	Foam Nitrile			

Knit Wrist

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.*

Cuff Style

*Sizing is partially based on preference which can vary by glove material and application.

	SIZE	WIDTH	LENDGH		
A	S	2-15/16"- 3-1/4" 74 mm-84 mm	6-3/4"- 7-1/4" 171 mm-183 mm		
	М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8' 193 mm-203 mm		
	L	3-13/16"- 4-1/4" 97 mm-107 mm	7-5/8"-8" 97 mm-107 mm		
	XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm		
	XXL	4-5/8''- 5' 216 mm-229 mm	4-5/8"- 5' 216 mm-229 mm		

RECOMMENDED APPLICATIONS

General purpose working

 Automotive Electronics

 Construction Mechanical



or visit www.maxglove.com