

## 20-550 MAX FLEXIBLE FOAM NITRILE GLOVES



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	Χ*
Tear	1	2	3	4	20	-
Puncture	1	2	3	4	-	_
Cut Resistance (TDM Test)	Α	В	С	D	Е	F

\*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Foam Nitrile Coating
Oil Resistant
Slip Resistant
Wear Resistant
Superior Dexterity



3/4 Knuckle Coating Better Protection

Logo Customization

15 Gauge Liner Highest dexterity

Knit Wrist Better fit

> Color-Coded Bands Distinguish sizes

## SPECIFICATIONS Gauge 15 Liner Material Nylon & Spandex Dip Material Foam Nitrile Cuff Style Knit Wrist

## **RECOMMENDED APPLICATIONS**

- Automotive
- Electronics
- Construction
- Mechanical
- General purpose working

MEASURE HAND AT
SPECIFIED POINTS AND
MATCH MEASUREMENT TO
APPROPRIATE SIZE RANGE.\*

\*Sizing is partially based on preference which can vary by glove material and application.

SIZE	WIDTH	LENDGH 6-3/4"- 7-1/4" 171 mm-183 mm		
S	<b>2-15/16"- 3-1/4"</b> 74 mm-84 mm			
М	3-1/4"- 3-13/16" 84 mm-97 mm	<b>7-1/4"-7-5/8'</b> 193 mm-203 mm		
L	<b>3-13/16"- 4-1/4"</b> 97 mm-107 mm	<b>7-5/8"-8"</b> 97 mm-107 mm		
XL	<b>4-1/2"- 4-5/8"</b> 107 mm-117 mm	<b>4-1/2"- 4-5/8"</b> 107 mm-117 mm		
XXL	<b>4-5/8"- 5'</b> 216 mm-229 mm	<b>4-5/8"- 5'</b> 216 mm-229 mm		

