

## 20-700 Economic Sandy Nitrile Gloves



| EN388 STANDARDS            |   |   |   |   |   |    |
|----------------------------|---|---|---|---|---|----|
| Abrasion                   | 1 | 2 | 3 | 4 | - | 1- |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | X* |
| Tear                       | 1 | 2 | 3 | 4 | - | -  |
| Puncture                   | 1 | 2 | 3 | 4 | 2 | -  |
| Cut Resistance (TDM Test)  | Α | В | С | D | Ε | F  |

\*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead





13 Gauge Liner Light & Breathable

Logo Customization


Knit Wrist Better fit

> Color-Coded Bands Distinguish sizes

## SPECIFICATIONS Gauge 13 Liner Material Polyester Dip Material Sandy Nitrile Cuff Style Knit Wrist

## **RECOMMENDED APPLICATIONS**

- Automotive
- Mechanical
- Construction
- Tools Handling



glove material and application.

| SIZE | WIDTH                                   | LENDGH                                 |  |  |
|------|---|--|--|--|
| S    | <b>2-15/16"- 3-1/4"</b><br>74 mm-84 mm  | <b>6-3/4"- 7-1/4"</b><br>171 mm-183 mm |  |  |
| М    | 3-1/4"- 3-13/16"<br>84 mm-97 mm         | <b>7-1/4"-7-5/8'</b><br>193 mm-203 mm  |  |  |
| L    | <b>3-13/16"- 4-1/4"</b><br>97 mm-107 mm | <b>7-5/8"-8"</b><br>97 mm-107 mm       |  |  |
| XL   | <b>4-1/2"- 4-5/8"</b><br>107 mm-117 mm  | <b>4-1/2"- 4-5/8"</b><br>107 mm-117 mm |  |  |
| XXL  | <b>4-5/8"- 5'</b><br>216 mm-229 mm      | <b>4-5/8"- 5'</b><br>216 mm-229 mm     |  |  |

