

30-200 **ANTI-STATIC PU GLOVES**



| EN388 | STAN | DARDS |
|--------------|------|-------|

| Abrasion | 1 | 2 | 3 | 4 | - | - |
|----------------------------|---|---|---|---|---|----|
| Cut Resistance (Coup Test) | | 2 | 3 | 4 | 5 | Х* |
| Tear | 1 | 2 | 3 | 4 | - | - |
| Puncture | 1 | 2 | 3 | 4 | - | - |
| Cut Resistance (TDM Test) | А | В | С | D | Е | F |

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead



RECOMMENDED APPLICATIONS

Knit Wrist Better Fit

| SPECIFICATIONS | | |
|----------------|--------------|--|
| Gauge | 13 | |
| Liner Material | Carbon Fiber | |
| Dip Material | PU | |
| Cuff Style | Knit Wrist | |

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.*

*Sizing is partially based on preference which can vary by glove material and application.

| SIZE | WIDTH | LENDGH | | | |
|------|---|--|--|--|--|
| S | 2-15/16"- 3-1/4" 74 mm-84 mm | 6-3/4"- 7-1/4" 171 mm-183 mm | | | |
| М | 3-1/4"- 3-13/16" 84 mm-97 mm | 7-1/4"-7-5/8' 193 mm-203 mm | | | |
| L | 3-13/16"- 4-1/4" 97 mm-107 mm | 7-5/8"-8" 97 mm-107 mm | | | |
| XL | 4-1/2"- 4-5/8" 107 mm-117 mm | 4-1/2"- 4-5/8" 107 mm-117 mm | | | |
| XXL | 4-5/8''- 5' 216 mm-229 mm | 4-5/8''- 5' 216 mm-229 mm | | | |

Electronics Tools handling

Manufacturing Mechanical



or visit www.maxglove.com