

40-200 **CUT RESISTANT SMOOTH NITRILE GLOVES**







EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	Х*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	21	_
Cut Resistance (TDM Test)	Α	В	С	D	Ε	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Smooth Nitrile Coating

Oil Resistant Water Resistant Abrasion Resistant



13 Gauge HPPE **Cut Resistant**

Logo Customization

Color-Coded Bands


Distinguishsizes

Knit Wrist Better fit

SPECIFICATIONS			
Gauge	13		
Liner Material	HPPE		
Dip Material	Smooth Nitrile		
Cuff Style	Knit Wrist		

RECOMMENDED APPLICATIONS

- Automotive
- Mechanical
- Metal Work
- Manufacturing



SIZE	WIDTH	LENDGH
S	2-15/16"- 3-1/4" 74 mm-84 mm	6-3/4"- 7-1/4" 171 mm-183 mm
М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8' 193 mm-203 mm
L	3-13/16"- 4-1/4" 97 mm-107 mm	7-5/8"-8" 97 mm-107 mm
XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm
XXL	4-5/8"- 5' 216 mm-229 mm	4-5/8"- 5' 216 mm-229 mm

