


40-250 **CUT RESISTANT FOAM NITRILE GLOVES**





EN388 STANDARDS							
Abrasion	1	2	3	4	-	-	
Cut Resistance (Coup Test)	1	2	3	4	5	Х*	
Tear	1	2	3	4	-	-	
Puncture	1	2	3	4	-	-	
Cut Resistance (TDM Test)	А	В	С	D	Е	F	

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead



SPECIFICATIONS		RECOMMENDED APPLICATIONS			
Gauge	13		AutomotiveElectronicsConstructionlMechanical		SEE
Liner Material	HPPE				
Dip Material	Foam Nitrile				MORE
Cuff Style	Knit Wrist				GLOVES
MEASURE HAND AT	$\cap \square \cap$	SIZE	WIDTH	LENDGH	
MATCH MEASUREMENT [.] APPROPRIATE SIZE RAN		S	2-15/16"- 3-1/4" 74 mm-84 mm	6-3/4"- 7-1/4" 171 mm-183 mm	
<		М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8' 193 mm-203 mm	
	A SI	L	3-13/16"- 4-1/4" 97 mm-107 mm	7-5/8"-8" 97 mm-107 mm	

*Sizing is partially based on preference which can vary by glove material and application.

SIZE	WIDTH	LENDGH
S	2-15/16"- 3-1/4" 74 mm-84 mm	6-3/4"- 7-1/4" 171 mm-183 mm
М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8' 193 mm-203 mm
L	3-13/16"- 4-1/4" 97 mm-107 mm	7-5/8''-8'' 97 mm-107 mm
XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm
XXL	4-5/8''- 5' 216 mm-229 mm	4-5/8''- 5' 216 mm-229 mm

or visit www.maxglove.com