


## 40-300 CUT RESISTANT PU GLOVES





| EN388 STANDARDS            |   |   |   |   |   |    |  |
|----------------------------|---|---|---|---|---|----|--|
| Abrasion                   | 1 | 2 | 3 | 4 | - | -  |  |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | X* |  |
| Tear                       | 1 | 2 | 3 | 4 | - | -  |  |
| Puncture                   | 1 | 2 | 3 | 4 | - | -  |  |
| Cut Resistance (TDM Test)  | А | В | С | D | Е | F  |  |

\*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead



| SPECIFICATIO   | ONS        |  | RECOMMENDE   | O APPLICATIONS |  |
|----------------|------------|--|--|----------------|--|
| Gauge          | 13         |  | <ul> <li>Construction</li> <li>Mechanical</li> <li>Metal Work</li> <li>Mining</li> </ul> |                |  |
| Liner Material | HPPE       |  |  |                |  |
| Dip Material   | PU         |  |  |                |  |
| Cuff Style     | Knit Wrist |  |  |                |  |

SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.

\*Sizing is partially based on preference which can vary by glove material and application.

| SIZE | WIDTH                                  | LENDGH                           |  |  |
|------|--|----------------------------------|--|--|
| S    | <b>2-15/16"- 3-1/4"</b><br>74 mm-84 mm | 6-3/4"- 7-1/4"<br>171 mm-183 mm  |  |  |
| М    | 3-1/4"- 3-13/16"<br>84 mm-97 mm        | 7-1/4"-7-5/8'<br>193 mm-203 mm   |  |  |
| L    | 3-13/16"- 4-1/4"<br>97 mm-107 mm       | <b>7-5/8"-8"</b><br>97 mm-107 mm |  |  |
| XL   | <b>4-1/2"- 4-5/8"</b><br>107 mm-117 mm | 4-1/2"- 4-5/8"<br>107 mm-117 mm  |  |  |
| XXL  | <b>4-5/8"- 5'</b><br>216 mm-229 mm     | 4-5/8"- 5'<br>216 mm-229 mm      |  |  |



or visit www.maxglove.com