



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Sandy Nitrile Coating
Oil Resistant
Excellent Grip
Abrasion Resistant

Crotch Reinforcement
More wear-resistant

Knit Wrist
Better fit



13 Gauge HPPE
Cut Resistant

TPR Reinforcement
High Impact Resistant


Adjustable Velcro
Better Protection

Color-Coded Bands
Distinguish sizes

SPECIFICATIONS	
Gauge	13
Liner Material	HPPE
Dip Material	Sandy Nitrile
Cuff Style	Knit Wrist

RECOMMENDED APPLICATIONS	
<ul style="list-style-type: none"> Automotive Mechanical Construction Tools Handling 	

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.*



*Sizing is partially based on preference which can vary by glove material and application.

SIZE	WIDTH	LENDGH
S	2-15/16" - 3-1/4" 74 mm-84 mm	6-3/4" - 7-1/4" 171 mm-183 mm
M	3-1/4" - 3-13/16" 84 mm-97 mm	7-1/4" - 7-5/8" 193 mm-203 mm
L	3-13/16" - 4-1/4" 97 mm-107 mm	7-5/8" - 8" 97 mm-107 mm
XL	4-1/2" - 4-5/8" 107 mm-117 mm	4-1/2" - 4-5/8" 107 mm-117 mm
XXL	4-5/8" - 5" 216 mm-229 mm	4-5/8" - 5" 216 mm-229 mm

SEE MORE GLOVES



or visit www.maxglove.com