

## 80-200 COW SPLIT LEATHER GLOVES



EN388	STAN	IDAR	DS	

MaxiPact

Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	Х*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	А	В	С	D	Е	F

\*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

**Cow Split Leather** Wear resistant Puncture resistant

Tear resistant

Canvas Material Comfortable & Breathable

> Knuckle Patch Better Protection

Logo Customization

## Safety Cuff Easy to take off

Easy to take off

## SPECIFICATIONS

Length	10.5 inches			
Back Material	Canvas			
Palm Material	Cow Split Leather			
Cuff Style	Safety Cuff			

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.\*

\*Sizing is partially based on preference which can vary by glove material and application.

SIZE	WIDTH	LENDGH
S	<b>2-15/16"- 3-1/4"</b> 74 mm-84 mm	<b>6-3/4"- 7-1/4"</b> 171 mm-183 mm
М	<b>3-1/4"- 3-13/16"</b> 84 mm-97 mm	<b>7-1/4"-7-5/8'</b> 193 mm-203 mm
L	<b>3-13/16"- 4-1/4"</b> 97 mm-107 mm	<b>7-5/8''-8''</b> 97 mm-107 mm
XL	<b>4-1/2"- 4-5/8"</b> 107 mm-117 mm	<b>4-1/2"- 4-5/8"</b> 107 mm-117 mm
XXL	<b>4-5/8"- 5'</b> 216 mm-229 mm	<b>4-5/8''- 5'</b> 216 mm-229 mm
	S M L XL	S 2-15/16"- 3-1/4" 74 mm-84 mm   M 3-1/4"- 3-13/16" 84 mm-97 mm   L 3-13/16"- 4-1/4" 97 mm-107 mm   XL 4-1/2"- 4-5/8" 107 mm-117 mm   XYI 4-5/8"- 5'

## RECOMMENDED APPLICATIONS

- Construction
- General Labour
- Metal Fabrication
- Landscaping





SCAN