



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

\*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

**Cow Split Leather**  
Wear resistant  
Puncture resistant  
Tear resistant

**Canvas Material**  
Comfortable  
Breathable

**Palm Reinforcement**  
More Wear-resistant  
Better Protection

**Fluorescent Fabric Reflective Webbing**  
High Visibility  
High Safety

**Safety Cuff**  
Easy to take off


**Logo Customization**



SPECIFICATIONS	
Length	10.5 inches
Back Material	Canvas
Palm Material	Cow Split Leather
Cuff Style	Safety Cuff

RECOMMENDED APPLICATIONS	
<ul style="list-style-type: none"> <li>Construction</li> <li>General Labour</li> <li>Metal Fabrication</li> <li>Landscaping</li> </ul>	

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.\*



\*Sizing is partially based on preference which can vary by glove material and application.

SIZE	WIDTH	LENGGH
S	2-15/16" - 3-1/4" 74 mm-84 mm	6-3/4" - 7-1/4" 171 mm-183 mm
M	3-1/4" - 3-13/16" 84 mm-97 mm	7-1/4" - 7-5/8" 193 mm-203 mm
L	3-13/16" - 4-1/4" 97 mm-107 mm	7-5/8" - 8" 97 mm-107 mm
XL	4-1/2" - 4-5/8" 107 mm-117 mm	4-1/2" - 4-5/8" 107 mm-117 mm
XXL	4-5/8" - 5" 216 mm-229 mm	4-5/8" - 5" 216 mm-229 mm

# SEE MORE GLOVES



or visit [www.maxglove.com](http://www.maxglove.com)