

EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tearing	1	2	3	4	-	-
Tearing	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead



Goat Grain Leather
Abrasion Resistant
Tear Resistant

Kevlar Stitching
Cut Resistant
Flame Retardant

Elastic cord
Better Fit

Cow Split Leather
Abrasion Resistant
Puncture Resistant
Heat Resistant


Extended Sleeve
Better Protection

Logo Customization

SPECIFICATIONS	
Length	14 / 16 / 18 inches
Hand Material	Goat Grain Leather
Sleeve Material	Cow Split Leather
Cuff Style	Open cuff

RECOMMENDED APPLICATIONS	
<ul style="list-style-type: none"> Welding Lumber Oil & Gas Metal Fabrication 	

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.*



*Sizing is partially based on preference which can vary by glove material and application.

SIZE	WIDTH	LENDGH
S	2-15/16" - 3-1/4" 74 mm-84 mm	6-3/4" - 7-1/4" 171 mm-183 mm
M	3-1/4" - 3-13/16" 84 mm-97 mm	7-1/4" - 7-5/8" 193 mm-203 mm
L	3-13/16" - 4-1/4" 97 mm-107 mm	7-5/8" - 8" 97 mm-107 mm
XL	4-1/2" - 4-5/8" 107 mm-117 mm	4-1/2" - 4-5/8" 107 mm-117 mm
XXL	4-5/8" - 5" 216 mm-229 mm	4-5/8" - 5" 216 mm-229 mm

SEE MORE GLOVES

SCAN

or visit www.maxglove.com