

| EN388 STANDARDS | | | | | | |
|----------------------------|---|---|---|---|---|----|
| Abrasion | 1 | 2 | 3 | 4 | - | - |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | X* |
| Tearing | 1 | 2 | 3 | 4 | - | - |
| Tearing | 1 | 2 | 3 | 4 | - | - |
| Cut Resistance (TDM Test) | A | B | C | D | E | F |

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Cow Split Leather
Abrasion Resistant
Puncture Resistant
Heat Resistant

Palm Reinforcement With Kevlar Sewing
More Wear Resistant
Better Protection

Knuckle Patch
Better Protection

With Lining Inside
Comfortable to wear

Long Sleeve
Better Protection


Logo Customization



| SPECIFICATIONS | |
|----------------|---------------------|
| Length | 14 / 16 / 18 inches |
| Liner Material | Cotton |
| Palm Material | Cow Split Leather |
| Cuff Style | Open cuff |

| RECOMMENDED APPLICATIONS | |
|---|--|
| <ul style="list-style-type: none"> Welding Lumber Oil & Gas Metal Fabrication | |

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.*



*Sizing is partially based on preference which can vary by glove material and application.

| SIZE | WIDTH | LENGGH |
|------|-----------------------------------|----------------------------------|
| S | 2-15/16" - 3-1/4" 74 mm-84 mm | 6-3/4" - 7-1/4" 171 mm-183 mm |
| M | 3-1/4" - 3-13/16" 84 mm-97 mm | 7-1/4" - 7-5/8" 193 mm-203 mm |
| L | 3-13/16" - 4-1/4" 97 mm-107 mm | 7-5/8" - 8" 97 mm-107 mm |
| XL | 4-1/2" - 4-5/8" 107 mm-117 mm | 4-1/2" - 4-5/8" 107 mm-117 mm |
| XXL | 4-5/8" - 5" 216 mm-229 mm | 4-5/8" - 5" 216 mm-229 mm |

SEE MORE GLOVES



or visit www.maxglove.com