

20-100 Oil Resistant Smooth Nitrile Gloves



EN388 STANDARDS						
Abrasion	1	2	3	4		1-1
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	27	-
Cut Resistance (TDM Test)	Α	В	С	D	Е	F


*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead



SPECIFICATIONS Gauge 13 Liner Material Polyester Dip Material Smooth Nitrile Cuff Style Knit Wrist

RECOMMENDED APPLICATIONS

- Automotive
- Mechanical
- Construction
- Manufacturing



glove material and application.

SIZE	WIDTH	LENDGH		
S	2-15/16"- 3-1/4" 74 mm-84 mm	6-3/4"- 7-1/4" 171 mm-183 mm		
М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8' 193 mm-203 mm		
L	3-13/16"- 4-1/4" 97 mm-107 mm	7-5/8"-8" 97 mm-107 mm		
XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm		
XXL	4-5/8"- 5' 216 mm-229 mm	4-5/8"- 5' 216 mm-229 mm		

