



| EN388 STANDARDS | | | | | | |
|----------------------------|---|---|---|---|---|----|
| Abrasion | 1 | 2 | 3 | 4 | - | - |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | X* |
| Tear | 1 | 2 | 3 | 4 | - | - |
| Puncture | 1 | 2 | 3 | 4 | - | - |
| Cut Resistance (TDM Test) | A | B | C | D | E | F |

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Foam Nitrile Coating
Oil Resistant
Slip Resistant
Wear Resistant
Superior Dexterity



Smooth Nitrile Fully Coating
Waterproof
All Around Protection

Logo Customization

15 Gauge Liner
Light & Breathable


Knit Wrist
Better fit

Color-Coded Bands
Distinguish sizes

| SPECIFICATIONS | |
|----------------|------------|
| Gauge | 15 |
| Liner Material | Polyester |
| Dip Material | Nitrile |
| Cuff Style | Knit Wrist |

| RECOMMENDED APPLICATIONS | |
|--|--|
| <ul style="list-style-type: none"> Automotive Mechanical Construction Tools Handling | |

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.*



*Sizing is partially based on preference which can vary by glove material and application.

| SIZE | WIDTH | LENDGH |
|------|-----------------------------------|----------------------------------|
| S | 2-15/16" - 3-1/4" 74 mm-84 mm | 6-3/4" - 7-1/4" 171 mm-183 mm |
| M | 3-1/4" - 3-13/16" 84 mm-97 mm | 7-1/4" - 7-5/8" 193 mm-203 mm |
| L | 3-13/16" - 4-1/4" 97 mm-107 mm | 7-5/8" - 8" 97 mm-107 mm |
| XL | 4-1/2" - 4-5/8" 107 mm-117 mm | 4-1/2" - 4-5/8" 107 mm-117 mm |
| XXL | 4-5/8" - 5" 216 mm-229 mm | 4-5/8" - 5" 216 mm-229 mm |

SEE MORE GLOVES



or visit www.maxglove.com