



EN388 STANDARDS

Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Sandy Nitrile Coating
Oil Resistant
Excellent Grip
Abrasion Resistant

Padded Palm Inside
Abrasion Resistant

Smooth Nitrile Coating
Liquid Resistant
More wear-resistant

Knit Wrist
Better fit



Crotch Reinforcement
More wear-resistant

TPR Reinforcement
Impact Resistant

13 Gauge HPPE
Cut Resistant

Adjustable Velcro
Better Protection

SPECIFICATIONS

Gauge	13
Liner Material	HPPE
Dip Material	Sandy Nitrile
Cuff Style	Knit Wrist

RECOMMENDED APPLICATIONS

- Automotive
- Mechanical
- Construction
- Drilling

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.*



*Sizing is partially based on preference which can vary by glove material and application.

SIZE	WIDTH	LENGGH
S	2-15/16" - 3-1/4" 74 mm-84 mm	6-3/4" - 7-1/4" 171 mm-183 mm
M	3-1/4" - 3-13/16" 84 mm-97 mm	7-1/4" - 7-5/8" 193 mm-203 mm
L	3-13/16" - 4-1/4" 97 mm-107 mm	7-5/8" - 8" 97 mm-107 mm
XL	4-1/2" - 4-5/8" 107 mm-117 mm	4-1/2" - 4-5/8" 107 mm-117 mm
XXL	4-5/8" - 5" 216 mm-229 mm	4-5/8" - 5" 216 mm-229 mm

SEE MORE GLOVES



or visit www.maxglove.com