

10-450 **THERMAL CRINKLE LATEX GLOVES**



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	-	_
Cut Resistance (TDM Test)	Α	В	С	D	Е	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Crinkle Latex Coating **Excellent Grip**

Abrasion Resistant

3/4 Knuckle Coating **Better Protection**

> **Polyester Terry Brushed** Keeps Warm

Logo Customization

Knit Wrist Better Fit




Color-Coded Bands Distinguishsizes

SPECIFICATIONS Gauge 7 Polyester Terry **Liner Material Dip Material** Crinkle Latex **Cuff Style** Knit Wrist

RECOMMENDED APPLICATIONS

- Construction
- Mechanical
- Warehouse
- Tools Handling



SIZE	WIDTH	LENDGH 6-3/4"- 7-1/4" 171 mm-183 mm		
S	2-15/16"- 3-1/4" 74 mm-84 mm			
М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8" 193 mm-203 mm 7-5/8"-8" 97 mm-107 mm		
L	3-13/16"- 4-1/4" 97 mm-107 mm			
XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm		
XXL	4-5/8"- 5' 216 mm-229 mm	4-5/8"- 5' 216 mm-229 mm		

