

20-540 MAX FLEXIBLE FOAM NITRILE GLOVES



EN388 STANDARDS						
Abrasion	1	2	3	4		1-1
Cut Resistance (Coup Test)	1	2	3	4	5	Χ*
Tear	1	2	3	4		-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	Α	В	С	D	Е	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Foam Nitrile Coating
Oil Resistant
Slip Resistant
Wear Resistant
Superior Dexterity



15 Gauge Liner Highest dexterity

Logo Customization

Knit Wrist Better fit

> Color-Coded Bands Distinguish sizes

SPECIFICATIONS Gauge 15 Liner Material Nylon & Spandex Dip Material Foam Nitrile Cuff Style Knit Wrist

RECOMMENDED APPLICATIONS

- Automotive
- Electronics
- Construction
- Mechanical
- General purpose working

MEASURE HAND AT
SPECIFIED POINTS AND
MATCH MEASUREMENT TO
APPROPRIATE SIZE RANGE.*

*Sizing is partially based on preference which can vary by glove material and application.

SIZE	WIDTH	LENDGH 6-3/4"- 7-1/4" 171 mm-183 mm		
S	2-15/16"- 3-1/4" 74 mm-84 mm			
М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8" 193 mm-203 mm 7-5/8"-8" 97 mm-107 mm		
L	3-13/16"- 4-1/4" 97 mm-107 mm			
XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm		
XXL	4-5/8"- 5' 216 mm-229 mm	4-5/8"- 5' 216 mm-229 mm		

