

MAX FLEXIBLE FOAM NITRILE GLOVES WITH DOTTED PALM



EN388 STANDARDS						
Abrasion	1	2	3	4		-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	Α	В	С	D	Ε	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Foam Nitrile Coating

Slip Resistant Wear Resistant Superior Dexterity



Fully Coating Better Protection

Logo Customization

15 Gauge Nylon Spandex Liner Highest Dexterity

Color-Coded Bands Distinguish Sizes

Knit Wrist Better Fit


Nitrile Dots More Non-slip

More Wear-resistant

SPECIFICATIONS				
Gauge	15			
Liner Material	Nylon & Spandex			
Dip Material	Foam Nitrile			
Cuff Style	Knit Wrist			

RECOMMENDED APPLICATIONS

- Automotive
- Electronics
- Construction
- Mechanical



SIZE	WIDTH	LENDGH 6-3/4"- 7-1/4" 171 mm-183 mm	
S	2-15/16"- 3-1/4" 74 mm-84 mm		
М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8' 193 mm-203 mm	
L	3-13/16"- 4-1/4" 97 mm-107 mm		
XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm	
XXL	4-5/8"- 5' 216 mm-229 mm	4-5/8"- 5' 216 mm-229 mm	

