

40-270 CUT RESISTANT SANDY NITRILE GLOVES







EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	21	-
Cut Resistance (TDM Test)	Α	В	С	D	Е	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Sandy Nitrile Coating
Oil Resistant
Excellent Grip
Abrasion Resistant



13 Gauge HPPE Cut Resistant

Logo Customization


Knit Wrist Better fit

Color-Coded Bands
Distinguish sizes

SPECIFICATIONS Gauge 13 Liner Material HPPE Dip Material Sandy Nitrile Cuff Style Knit Wrist

RECOMMENDED APPLICATIONS

- Automotive
- Mechanical
- Construction!
- Tools Handling



SIZE	WIDTH	LENDGH 6-3/4"- 7-1/4" 171 mm-183 mm		
S	2-15/16"- 3-1/4" 74 mm-84 mm			
М	3-1/4"- 3-13/16" 84 mm-97 mm	7-1/4"-7-5/8' 193 mm-203 mm		
L	3-13/16"- 4-1/4" 97 mm-107 mm	7-5/8"-8" 97 mm-107 mm		
XL	4-1/2"- 4-5/8" 107 mm-117 mm	4-1/2"- 4-5/8" 107 mm-117 mm		
XXL	4-5/8"- 5' 216 mm-229 mm	4-5/8"- 5' 216 mm-229 mm		

