



| EN388 STANDARDS            |   |   |   |   |   |    |
|----------------------------|---|---|---|---|---|----|
| Abrasion                   | 1 | 2 | 3 | 4 | - | -  |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | X* |
| Tear                       | 1 | 2 | 3 | 4 | - | -  |
| Puncture                   | 1 | 2 | 3 | 4 | - | -  |
| Cut Resistance (TDM Test)  | A | B | C | D | E | F  |

\*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead



**Sandy Nitrile Coating**  
Oil Resistant  
Excellent Grip  
Abrasion Resistant

**Smooth Nitrile Fully Coating**  
Water Resistant

**Logo Customization**

**13 Gauge HPPE Cut Resistant**


**Knit Wrist**  
Better fit

**Color-Coded Bands**  
Distinguish sizes

| SPECIFICATIONS |               |
|----------------|---------------|
| Gauge          | 13            |
| Liner Material | HPPE          |
| Dip Material   | Sandy Nitrile |
| Cuff Style     | Knit Wrist    |

| RECOMMENDED APPLICATIONS   |  |
|--|--|
| <ul style="list-style-type: none"> <li>Automotive</li> <li>Mechanical</li> <li>Construction</li> <li>Tools Handling</li> </ul> |  |

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.\*



\*Sizing is partially based on preference which can vary by glove material and application.

| SIZE | WIDTH                             | LENDGH                           |
|------|-----------------------------------|----------------------------------|
| S    | 2-15/16" - 3-1/4"<br>74 mm-84 mm  | 6-3/4" - 7-1/4"<br>171 mm-183 mm |
| M    | 3-1/4" - 3-13/16"<br>84 mm-97 mm  | 7-1/4" - 7-5/8"<br>193 mm-203 mm |
| L    | 3-13/16" - 4-1/4"<br>97 mm-107 mm | 7-5/8" - 8"<br>97 mm-107 mm      |
| XL   | 4-1/2" - 4-5/8"<br>107 mm-117 mm  | 4-1/2" - 4-5/8"<br>107 mm-117 mm |
| XXL  | 4-5/8" - 5"<br>216 mm-229 mm      | 4-5/8" - 5"<br>216 mm-229 mm     |

**SEE MORE GLOVES**

SCAN

or visit [www.maxglove.com](http://www.maxglove.com)