



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tear	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

\*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead



**Foam Latex Coating**  
Soft & Good Grip  
Abrasion Resistant  
Tear Resistant

**Smooth Latex Fully Coating**  
Water Resistant

**Knit Wrist**  
Better Fit

**Logo Customization**

**15G Polyester Liner**  
More Comfortable


**Acrylic Terry Brushed**  
Cold Protection

**Color-Coded Bands**  
Distinguish Sizes

SPECIFICATIONS	
Gauge	15 & 10
Liner Material	Polyester & Acrylic
Dip Material	Foam Latex
Cuff Style	Knit Wrist

RECOMMENDED APPLICATIONS	
<ul style="list-style-type: none"> <li>Construction</li> <li>Land scaping</li> <li>Warehouse</li> <li>Garden Work</li> </ul>	

MEASURE HAND AT SPECIFIED POINTS AND MATCH MEASUREMENT TO APPROPRIATE SIZE RANGE.\*



\*Sizing is partially based on preference which can vary by glove material and application.

SIZE	WIDTH	LENDGH
S	2-15/16" - 3-1/4" 74 mm-84 mm	6-3/4" - 7-1/4" 171 mm-183 mm
M	3-1/4" - 3-13/16" 84 mm-97 mm	7-1/4" - 7-5/8" 193 mm-203 mm
L	3-13/16" - 4-1/4" 97 mm-107 mm	7-5/8" - 8" 97 mm-107 mm
XL	4-1/2" - 4-5/8" 107 mm-117 mm	4-1/2" - 4-5/8" 107 mm-117 mm
XXL	4-5/8" - 5" 216 mm-229 mm	4-5/8" - 5" 216 mm-229 mm

**SEE MORE GLOVES**




or visit [www.maxglove.com](http://www.maxglove.com)