

10-420 **THERMAL CRINKLE LATEX GLOVES**



| EN388 STANDARDS | | | | | | |
|----------------------------|---|---|---|---|----|----|
| Abrasion | 1 | 2 | 3 | 4 | - | - |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | Χ* |
| Tear | 1 | 2 | 3 | 4 | - | - |
| Puncture | 1 | 2 | 3 | 4 | 21 | - |
| Cut Resistance (TDM Test) | Α | В | С | D | Ε | F |

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

Crinkle Latex Coating

Excellent Grip Abrasion Resistant

Thumb Coating

Better Protection

Acrylic Terry Brushed Keeps Warm

Logo Customization

Knit Wrist Better fit




Color-Coded Bands Distinguishsizes

SPECIFICATIONS Gauge 10 Acrylic Terry **Liner Material Dip Material** Crinkle Latex **Cuff Style** Knit Wrist

RECOMMENDED APPLICATIONS

- Construction
- Mechanical
- Warehouse
- Tools Handling



| SIZE | WIDTH | LENDGH 6-3/4"- 7-1/4" 171 mm-183 mm | | |
|------|---|---|--|--|
| S | 2-15/16"- 3-1/4" 74 mm-84 mm | | | |
| М | 3-1/4"- 3-13/16" 84 mm-97 mm | 7-1/4"-7-5/8' 193 mm-203 mm | | |
| L | 3-13/16"- 4-1/4" 97 mm-107 mm | 7-5/8"-8" 97 mm-107 mm | | |
| XL | 4-1/2"- 4-5/8" 107 mm-117 mm | 4-1/2"- 4-5/8" 107 mm-117 mm | | |
| XXL | 4-5/8"- 5' 216 mm-229 mm | 4-5/8"- 5' 216 mm-229 mm | | |

