

80-300 COW SPLIT LEATH GLOVES REINFORCED PALM



| EN388 STANDARDS | | | | | | |
|----------------------------|---|---|---|---|---|-----|
| Abrasion | 1 | 2 | 3 | 4 | | 1-1 |
| Cut Resistance (Coup Test) | 1 | 2 | 3 | 4 | 5 | Χ* |
| Tear | 1 | 2 | 3 | 4 | - | - |
| Puncture | 1 | 2 | 3 | 4 | - | _ |
| Cut Resistance (TDM Test) | Α | В | С | D | Ε | F |


*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead



| SPECIFICATIONS | | | | |
|----------------|-------------------|--|--|--|
| Length | 10.5 inches | | | |
| Back Material | Canvas | | | |
| Palm Material | Cow Split Leather | | | |
| Cuff Style | Safety Cuff | | | |

RECOMMENDED APPLICATIONS

- Construction
- General Labour
- Metal Fabrication
- Landscaping



glove material and application.

| SIZE | WIDTH | LENDGH |
|------|---|--|
| S | 2-15/16"- 3-1/4" 74 mm-84 mm | 6-3/4"- 7-1/4" 171 mm-183 mm |
| М | 3-1/4"- 3-13/16" 84 mm-97 mm | 7-1/4"-7-5/8' 193 mm-203 mm |
| L | 3-13/16"- 4-1/4" 97 mm-107 mm | 7-5/8"-8" 97 mm-107 mm |
| XL | 4-1/2"- 4-5/8" 107 mm-117 mm | 4-1/2"- 4-5/8" 107 mm-117 mm |
| XXL | 4-5/8"- 5' 216 mm-229 mm | 4-5/8"- 5' 216 mm-229 mm |

